




POST MILES SHEET TOTAL TOTAL PROJECT NO. SHEETS



EXCAVATION







OG or grading plane

IN TRENCH


BACKFILL


BACKFILL


EXCAVATION

EXCAVATION

 \sim \sim








Embankment constructed

prior to excavation



IN EMBANKMENT METAL AND PLASTIC PIPES AND CORRUGATED METAL PIPE ARCHES 84" or Smaller

NOTES:

IN EMBANKMENT STRUCTURAL STEEL PLATE PIPE ARCHES

- PIPES: 30" minimum for diameters up to and including 42" then $\frac{2}{3}$ diameter but no more than 60" required. CORRUGATED METAL PIPE ARCHES: 30" maximum.
- 2. 3/3 H up to 60" maximum.
- Slope or shore excavation sides as necessary.
- Backfill shall be placed full width of excavation except as noted.

DIST COUNTY

- 5. Diagrams do not apply to overside drains.
- 6. Dimensions shown are minimum.
- For strutting requirement of structural steel plate pipe, arches and vehicular undercrossing during construction, see Standard Plan D88A.

LEGEND

Structure Excavation (Culvert)

Structure Backfill (Culvert) 95% Relative Compaction

STATE OF CALIFORNIA
DEPARTMENT OF TRANSPORTATION

EXCAVATION AND BACKFILL METAL AND PLASTIC CULVERTS

NO SCALE

A62F